

WHAT IS CLAIMED IS:

1. An apparatus comprising:
- an examination arm with, at one end thereof, an image receiver and a radiation delivery head at the other end,
 - a support on which the arm is mounted;
 - the arm being mounted for rotation about a first axis substantially perpendicular to the direction of the examination arm and passing through the center of an examination position;
 - the arm being further mounted for rotation about a second horizontal axis substantially perpendicular to the first axis and to the examination arm; and
 - a support column on which the support can be moved up and down vertically.
2. The apparatus of claim 1 wherein the examination arm is mounted on a support for rotation about the second axis via a C-shaped arm.
3. The apparatus of claim 1 wherein the examination arm is mounted for rotation about the second axis with a range of angular travel varying from a vertical position to a horizontal position.
4. The apparatus of claim 2 wherein the examination arm is mounted for rotation about the second axis with a range of angular travel varying from a vertical position to a horizontal position.
5. The apparatus of claim 1 wherein the examination arm is mounted for rotation about the first axis with a range of angular travel greater than or equal to 180° at both sides of a vertical position of the examination arm.
6. The apparatus of claim 2 wherein the examination arm is mounted for rotation about the first axis with a range of angular travel greater than or equal to 180° at both sides of a vertical position of the examination arm.

7. The apparatus of claim 3 wherein the examination arm is mounted for rotation about the first axis with a range of angular travel greater than or equal to 180° at both sides of a vertical position of the examination arm.

8. A method for taking images of an object with an apparatus comprising:

an examination arm with, at one end thereof, an image receiver and a radiation delivery head at the other end;

a support on which the arm is mounted the arm being mounted for rotation about a first axis substantially perpendicular to the direction of the examination arm and passing through the center of a breast examination position,

the arm being further mounted for rotation about a second horizontal axis substantially perpendicular to the first axis and to the examination arm;

a support column on which the support can be moved up and down vertically;

comprising the steps of:

adjusting the position of the support on the support column and the angular position of the examination arm about the second axis;

adjusting the angular position of the examination arm about the first axis; and

positioning the object and taking the images.

9. The method of claim 8 comprising the steps of:

releasing the object;

changing the angular position of the support arm about the first axis;

and

installing the object and taking the images.

Sub
AI
Cm
10033868-11901
T06T2" 8988800T

10. The method of claim 8 wherein the angular rotation of the examination arm about the first axis defines a vertical plane.

11. The method of claim 9 wherein the angular rotation of the examination arm about the first axis defines a vertical plane.

12. The method of claim 8 wherein the angular rotation of the examination arm about the first axis defines an inclined plane.

13. The method of claim 9 wherein the angular rotation of the examination arm about the first axis defines an inclined plane.

14. The method of claim 8 wherein angular rotation of the examination arm about the first axis defines a horizontal plane.

15. The method of claim 9 wherein angular rotation of the examination arm about the first axis defines a horizontal plane.

Sub
AI
encl

10033868-121901